



Conductivity sensor kit, stainless steel, 1" NPT, 24" probes, 110 VAC level controller

» Conductivity Sensor Series » Conductivity sensor kit, stainless steel, 1" NPT, 24" probes, 110 VAC level controller



M3784

Applications:

- Environments such as semi-solid liquids, industrial slurries and wastewater
- Water-based liquids

Related Products:



M3784-220 (220VAC)



M3784-24 (24VAC)



Sensing Solutions since 1959

Model # M3784-110 Technical Data Sheet

Conductivity sensor kit, stainless steel, 1" NPT, 24" probes, 110 VAC level controller

Specifications:

Input Voltage	110 VAC
Length Total	24" length (Standard); 72" length (Maximum, with two extensions). May be cut to custom length
Max Pressure	30 PSI
Max Temperature	212°F (100°C)
Mounting	1" NPT
Note	- Integral junction box with IP68 (NEMA 6) protection 10' cable for attaching sensing head to controller. - Optional extension kit available, includes 3-25" probe extensions, p/n 005-M03797-EXT
Other Wetted Materials	316 Stainless Steel electrodes; Polypropylene housing. All food-grade materials



BEP-Bestobell / Bestobell-Aquatronix
2880 Argentia Road, Unit 3
Mississauga, ON, L5N 7X8
Tel. 905-826-1953 / Fax 905-826-1778
www.bestobell.com

BEP-Bestobell / Bestobell-Aquatronix
970 Montée de Liesse, #204
St. Laurent, QC, H4T 1W7
Tél. 514-331-1225 / Fax 514-331-4255
www.bestobell.com

BEP-Bestobell / Bestobell-Aquatronix
166 North Side Road
Riverport, NS, B0J 2W0
Tel. 902-766-0220/ Fax 514-331-4255
www.bestobell.com

Model # R2-120 Technical Data Sheet

Controller, 120VAC, SPDT, for pump level



Applications:

- Automatic liquid level control
- Easily configurable for two Level differential, single point protection or alarm operations
- For 120VAC input signals

Specifications:

Electrical Connectors	Direct Wire Screw Terminals
Electrical Ratings	12 VAC Sensing Voltage, 10 Amps @ 120 VAC (1/5 HP), 10 Amps @ 30 VDC
Input Types	Adjustable Probe Conductivity from 1 - 100K Ohms
Input Voltage	120 VAC
Mounting	Slots for #8 screws, 2 places
Type	1 Form C (SPDT) Single Pole - Double Throw